


TECHNICAL DATA SHEET



Last Updated February 2018

Roll-on Tile Basecoat

Description **Roll-on Tile** - Basecoat is composed of a high performance pure acrylic binder containing finely graded quartz sand and durable colour pigments, along with incorporated powerful mould and fungus inhibitors. **Roll-on Tile** - Basecoat is a sand based texture paint, that can be left off the roller or crosshatched with a water brush to achieve a subtle variegated style finish. Additional colours can be blended in during finishing to achieve an attractive shaded / patina finish if required

Features

• 5 year warranty* • Water based • Ease of use • Vapour permeable

Benefits

Tough • Flexible • Water resistant • Excellent adhesion • Long term exterior protection • Can minimise surface imperfections • No hot tyre pickup when topcoated with Roll-on Tile-Glaze

Uses **Roll-on Tile** - Basecoat is suitable for application over properly prepared substrates such as concrete, cement sheeting. Can be used interior & exterior • Primarily for decoration and protection of surfaces but can also camouflage minor imperfections within a substrate. Can be over coated with **Roll-on Tile** - Glaze, for added durability and lower maintenance

Colours and Gloss Can be tinted to a wide range of colours, from soft natural tones to strong vibrant colours

•Satin Sheen when over coated with **Roll-on Tile** - Glaze

Sheen Level Matt

Typical Data at 25°C and 50% Relative Humidity


Thinning	Not required when using over Roll-on Tile – Primer
Coverage Rate	Coverage rates may vary according to the condition of the substrate, desired finish or method of application. Roll-on Tile - Basecoat is usually applied at the rate of approximately 3.5 to 4.5 square meters per litre and with a minimum film build of 200 microns. Care must be taken to avoid excessive build-up in corners and edges.
Drying Time	5 hours
Touch Dry	2 hours
Dry to Recoat	5 hours
Crack Bridging	Excellent
Abrasion Resistance	Excellent
Usual No Coats	2 to 3
Packaging Sizes	15lt and 10lt Pails
Clean Up	Water

Substrate Conditions **Roll-on Tile** - Basecoat must be applied over properly prepared substrates that are free of dirt, dust, grime and any other contaminants. Substrates must not contain more than 15% moisture prior to the application of **Roll-on Tile** – Basecoat. Do not apply **Roll-on Tile** - Basecoat if air and surface temperatures are below 5°C or above 35°C. If applying over fresh cementitious substrates such as concrete must be left for up to 28 days to sufficiently cure prior to application of **Roll-on Tile** – Basecoat. **Roll-on Tile** - Primer should be used when applying over bare cured concrete surfaces

Mixing Stir thoroughly before use with drill mixer or hand paint whacker until consistently mixed

Application The application of **Roll-on Tile** - Basecoat should be carried out per instruction procedure and should only be carried out in accordance with **Roll-on Tile** - Basecoat specifications. If using multiple pails of **Roll-on Tile** - Basecoat contents must be boxed together to ensure colour

TECHNICAL DATA SHEET



Last Updated February 2018

Roll-on Tile Basecoat

consistency. Be sure to keep a wet edge with this product and plan your work to suit the product and weather conditions. If joining up to previous day's application, it is "good working practice" to start and finish on an expansion joint. Keep the finished **Roll-on Tile** - Basecoat sheltered from rain & moisture for 24 - 48 hrs after completion dependent on climatic conditions. Best rolled on with a long nap sheepskin roller then re-rolled achieve desired even finish. Can brush through additional colour blends while basecoat is wet to achieve a variegated finish if desired.

Safety Data

Refer to **Roll-on Tile** - Basecoat SDS

Precautions and Limitations

- **Roll-on Tile** - Basecoat should not be applied in temperatures below 5°C or above 35°C
- **Roll-on Tile** - Basecoat is not suitable for areas of continual damp or areas submerged in water

Transport and Storage

- Store in a cool dark place • Keep pail sealed • Do not stack over 3 high

Disposal

- Dispose of in accordance with local council regulations

Disclaimer

Roll-on Tile will not accept responsibility for any misuse of this product or if not applied in accordance with our technical specifications. Due to our policy of continuing product improvement, **Roll-on Tile** reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

* WHEN USED AS PART OF A FULL **Roll-on Tile** SYSTEM.